



High Speed Steel PARALLEL SHANK TWIST DRILLS Jobber Series

Specifications conform to
IS 5101-1991
ISO 235-1980
DIN 338 - 1978
BS 328 : Part 1 : 1986
Dimensions in mm / inch



Diameter h8			Flute Length	Overall Length
mm	inch	Number Series		
0.30	-		3	19
0.40	1/64		5	20
0.50	-		6	22
0.60	-		7	24
0.70	-		9	28
0.80	1/32	68, 67, 66	10	30
0.90	-	65, 64, 63	11	32
1.00	-	62, 61, 60, 59	12	34
1.10	-	58, 57	14	36
1.20	3/64	56	16	38
1.30	-	55	16	38
1.40	-	54	18	40
1.50			18	40
1.60	1/16	53, 52	20	43
1.70			20	43
1.80		51, 50	22	46
1.90		49	22	46
2.00	5/64	48, 47	24	49
2.10		46, 45	24	49
2.20		44	27	53
2.30		43	27	53
2.40	3/32	42, 41	30	57
2.50		40, 39	30	57
2.60		38, 37	30	57
2.70		36	33	61

Diameter h8			Flute Length	Overall Length
mm	inch	Number Series		
2.80	7/64	35, 34	33	61
2.90		33, 32	33	61
3.00			33	61
3.10		31	36	65
3.20	1/8		36	65
3.30		30	36	65
3.40			39	70
3.50		29	39	70
3.60	9/64	28	39	70
3.70		27, 26	39	70
3.80		25	43	75
3.90		24, 23	43	75
4.00	5/32	22, 21	43	75
4.10		20	43	75
4.20		19	43	75
4.30		18	47	80
4.40	11/64	17	47	80
4.50		16	47	80
4.60		15, 14	47	80
4.70		13	47	80
4.80	3/16	12	52	86
4.90		11, 10	52	86
5.00		9	52	86
5.10		8, 7	52	86
5.20	13/64	6, 5	52	86



High Speed Steel PARALLEL SHANK TWIST DRILLS Jobber Series

Specifications conform to
IS 5101-1991
ISO 235-1980
DIN 338 - 1978
BS 328 : Part 1 : 1986
Dimensions in mm / inch



Diameter h8			Flute Length	Overall Length
mm	inch	Number & Letter Series		
5.30			52	86
5.40		4, 3	57	93
5.50			57	93
5.60	7/32	2	57	93
5.70			57	93
5.80		1	57	93
5.90		A	57	93
6.00	15/64		57	93
6.10		B, C	63	101
6.20		D	63	101
6.30			63	101
6.40	1/4	E	63	101
6.50		F	63	101
6.60		G	63	101
6.70			63	101
6.80	17/64	H	69	109
6.90		I	69	109
7.00		J	69	109
7.10	9/32	K	69	109
7.20			69	109
7.30			69	109
7.40		L	69	109
7.50		M	69	109
7.60	19/64		75	117
7.70		N	75	117
7.80			75	117
7.90	5/16		75	117
8.00		O	75	117
8.10			75	117
8.20		P	75	117
8.30	21/64		75	117
8.40		Q	75	117
8.50			75	117

Diameter h8			Flute Length	Overall Length
mm	inch	Number & Letter Series		
8.60		R	81	125
8.70	11/32		81	125
8.80		S	81	125
8.90			81	125
9.00			81	125
9.10	23/64	T	81	125
9.20			81	125
9.30		U	81	125
9.40			81	125
9.50			81	125
9.60	3/8	V	87	133
9.70			87	133
9.80		W	87	133
9.90	25/64		87	133
10.00			87	133
10.10		X	87	133
10.20			87	133
10.30	13/32	Y	87	133
10.40			87	133
10.50		Z	87	133
10.60		-	87	133
10.70	27/64	-	94	142
10.80		-	94	142
10.90		-	94	142
11.00		-	94	142
11.10	7/16	-	94	142
11.20		-	94	142
11.30		-	94	142
11.40		-	94	142
11.50	29/64	-	94	142
11.60		-	94	142
11.70		-	94	142
11.80		-	94	142



High Speed Steel **PARALLEL SHANK TWIST DRILLS** **Jobber Series**

Specifications conform to
 IS 5101-1991
 ISO 235-1980
 DIN 338 - 1978
 BS 328 : Part 1 : 1986
 Dimensions in mm / inch



Diameter h8		Flute Length	Overall Length
mm	inch		
11.90	15/32	101	151
12.00		101	151
12.10		101	151
12.20		101	151
12.30	31/64	101	151
12.40		101	151
12.50		101	151
12.60		101	151
12.70	1/2	101	151
12.80		101	151
12.90		101	151
13.00		101	151
13.10	33/64	101	151
13.20		101	151
13.30		108	160
13.40		108	160
13.50	17/32	108	160

Diameter h8		Flute Length	Overall Length
mm	inch		
13.60		108	160
13.70		108	160
13.80		108	160
13.90	35/64	108	160
14.00		108	160
14.25	9/16	114	169
14.50		114	169
14.75	37/64	114	169
15.00		114	169
15.25	19/32	120	178
15.50	39/64	120	178
15.75		120	178
16.00	5/8	120	178
17.00		125	184
18.00	11/16	130	191
19.00		135	198
20.00	3/4	140	205